

TA Fast-Fit is our newest prefabricated product for use with small terminal units in both heating and cooling applications

Key advantages over traditional installations:



Faster installation on site



Easy setting and sizing with PIBCV ensures total control



Reducing the risk of leakage and installation errors



Time saving on system commissioning



Highly reliable

Fully assembled and factory pressure tested to ensure reliability

Easy Installation

Each unit comes ready to install and uniquely labelled saving time on site

>

Quick hydronic balancing

The pressure independent solution provides direct setting of the max flow



Precise flow control

The modulating version provides uniquely shaped EQM characteristic for best modulating control



TA Fast-Fit -Prefabricated solution for terminal units

- Size Range 1/2" 11/4"
- Bypass (for flushing & isolation) / test-point / drain / strainer on flow
- PIBCV & Actuator on the return to aid with balancing & control




Making system commissioning hassle-free

Normal operation




Flushing the distribution system



1. Closed 2. Closed 3. Open 4. Closed

Back flushing



3. Open

4. Open


4. Open

Forward flushing

2. Open

1. Closed

1. Open



3. Closed

| Actuators / Hoses / Adapters

Selection of accessories available for the Fast-Fit solution.

Accessories		Compatible TA Fast-Fit product
	TA-Slider 160 For Modulating Control *included with the TA Fast-Fit	TA-Fast-Fit with PIBCV TA-Modulator ½" - 1¼ TA-Fast-Fit with PIBCV TA-Compact-P ½" - 1¼
4	FHA1 Hose	TA-Fast-Fit with PIBCV TA-Modulator ½" - 1¼ TA-Fast-Fit with PIBCV TA-Compact-P ½" - 1¼
	SWT Conn. Adapters	TA-Fast-Fit with PIBCV TA-Modulator ½" - 1¼ TA-Fast-Fit with PIBCV TA-Compact-P ½" - 1¼

I How can we help you?

